



SS Clean 33

Acidic Cleaner

SS Clean 33 is an acidic compound for cleaning, removing oxides and preparing metals for painting.

Use for removing shop dirt, oils, light grease rust, oxides, flux and heat scale in preparing metals for painting. SS Clean 33 will clean aluminum and condition it for conversion processing. Use for cleaning stainless steel to remove dirt and embedded soils in the metal.

SS Clean 33 may be used by tank immersion, wipe on or spray on methods.

TANK IMMERSION:

Dilute SS Clean 33 with water to 5 to 25% by volume. Immerse pieces in a warm (80° - 140°F) solution. Follow by rinsing and drying before further actions.

WIPE ON APPLICATION:

Dilute SS Clean 33 with water to 10 to 50% by volume. Apply with rags or brushes at room temperature. Allow soaking 2 to 20 minutes, then rinsing and wiping dry.

SPRAY APPLICATION:

Dilute SS Clean 33 with water to 10 to 50% by volume. Apply a coarse spray at room temperature. Apply sufficient dilute SS Clean 33 to a slight run-off. Allow soaking 2 to 20 minutes, then rinsing and wiping dry.

PACKAGING:

SS Clean 33 is available in, 5 gallon jugs, 30 gallon mini Drums, 55 gallon Drums and 275 gallon Pallet Totes.

Note that the above summary is not a replacement for label directions. As with all products read and follow the label directions carefully.

27536 CR 561 ---- Tavares FL, 32778

352/343-3484

352/343-0083 FAX